
PCI-1762

16-ch Relay and 16-ch Isolated **Digital Input PCI Card**



Features

- 16 opto-isolated digital input channels
- 16 relay actuator output channels
- LED indicators to show activated relays
- Jumper selectable dry contact/wet contact input signals
- BoardID switch



Introduction

The PCI-1762 provides 16 opto-isolated digital inputs with isolation protection of 2,500 Vpc for collecting digital inputs in noisy environments, 16 relay actuators that can be used as a on/off control devices or small power switches.

For easy monitoring, each relay is equipped with one red LED to show its on/off status. Each isolated input supports both dry contact and wet contact so that it can easily interface with other devices when no voltage is present in the external circuit.

Specifications

Isolated Digital Input

Channels

 Input Voltage Logic 0: 3.0 V max.

Logic 1: 10 V min. (50 V max.)

 Interrupt Capable Ch. 2 (IDI0,IDI8) Isolation Protection 2.500 Vpc ■ Opto-Isolator Response 100 µs Input Resistance 5.7 k Ohm 1 W

Relay Output

Channels

 Relay Type Form A or Form B (Jumper selectable) Contact Rating 0.5 A @ 250 V_{AC}, 0.5 A @ 30 V_{DC}

• Max. Switching Power 125 VA, 15 W Max. Switching Voltage 250 V_{AC}, 220 V_{DC} Operate Time Typical: 3 ms, Max.: 5 ms Release Time Typical: 2 ms, Max.: 4 ms Resistance Contact: 50 m Ohm max. 2 x 10⁵ cycles min. @ 0.5A/ 250V_{AC} Life Expectancy

General

I/O Connectors 1 x DB62 female connector Dimensions (L x H) 175 x 100 mm (6.9" x 3.9") Power Consumption Typical: 5 V @ 250 mA Max.: 5 V @ 620 mA • Operating Temperature $0 \sim 60^{\circ}\text{C} (32 \sim 140^{\circ}\text{F})$

 Storage Temperature -20 ~ 70°C (-4 ~ 158°F) Storage Humidity 5 ~ 95 % RH, non-condensing

Ordering Information

PCI-1762 16-ch Relay and 16-ch Isolated Digital Input PCI Card

Accessories

 PCL-10162-1E DB62 Cable, 1 m PCL-10162-3E DB62 Cable, 3 m

 ADAM-3962 DB62 DIN-rail Wiring Board

ADVANTECH