

UNO-2171

Intel® Pentium® M/Celeron® M Automation Computer with 2 x LAN, 4 x COM, PC/104+



Features

- Onboard Pentium® M 1.4 GHz or Celeron® M 1.0 GHz
- Onboard 512 KB battery-backup SRAM
- Two RS-232 and two RS-232/422/485 ports with automatic flow control
- Two 10/100Base-T RJ-45 ports
- Audio with Mic in, Line in, Line out
- 2 x USB 2.0 ports
- PC/104+ expansion slots
- Windows® CE 5.0 & 6.0, Windows XP Embedded, WES2009, and Linux ready
- Onboard system status LED indicators
- Supports Wake on LAN and Boot from LAN function
- Fanless design with no internal cabling
- Isolation between chassis and power ground

Introduction

UNO-2171 is an embedded automation computer that supports PC/104+ expansion, serial communication ports and several other networking interfaces. UNO-2171 supports Windows XP Embedded OS and Windows CE 5.0 & 6.0, which offers a pre-configured image with optimized onboard device drivers. Windows XP Embedded delivers the power of the Windows operating system in componentized form. You can seamlessly integrate your applications into Windows XP Embedded and speed up your system development with an application ready platform that can provide a rich networking interface to fulfill diverse requirements.

Specifications

General

- **Certifications** CE, FCC class A, UL, CCC
- **Dimensions (W x D x H)** 255 x 152 x 59 mm (10" x 6.0" x 2.3")
- **Enclosure** Aluminum
- **Mounting** Wallmount
- **Industrial Grounding** Isolation between chassis and power ground
- **Power Consumption** 24 W (Typical)
- **Power Requirements** 10 ~ 53 V_{dc} (e.g. +24 V @ 2 A) (Min. 48 W), ATX
- **Weight** 2.4 kg (Typical)
- **OS Support** WES Windows XP Embedded, WES2009, Windows 2000/XP, Windows CE 5.0 & 6.0, Linux, QNX
- **System Design** Fanless with no internal cabling
- **Remote Management** Built-in Advantech DiagAnywhere agent on Windows CE / XPe

System Hardware

- **CPU** Pentium M 1.4 GHz, Celeron M 1.0 GHz
- **Memory** 512 MB/1 GB DDR SDRAM built-in
- **Battery Backup SRAM** 512 KB
- **Indicators** LEDs for Power, IDE, Alarm for battery backup SRAM, LAN (Active, Status) and Serial (Tx, Rx)
- **Keyboard/Mouse** 1 x PS/2
- **PC/104 Slot** PC/104+ slot, Supports +5 & 3.3 V Power
- **Storage** SSD: 2 x internal type I/II CompactFlash® slot
HDD: Build-in one 2.5" SATA/IDE HDD bracket
DB15 VGA connector, 1600 x 1200 @ 85 Hz
- **Display**
- **Audio** Mic in, Line in, Line out
- **Watchdog Timer** Programmable 256 levels timer interval, from 1 to 255 sec

I/O Interface

- **Serial Ports** 2 x RS-232, 2 x RS-232/422/485 with DB9 connectors
Automatic RS-485 data flow control
- **Serial Port Speed** RS-232: 50 ~ 115.2 kbps
RS-422/485: 50 ~ 921.6 kbps (Max.)
- **LAN** 2 x 10/100Base-T RJ-45 ports (supports wake on LAN and built-in boot ROM in flash BIOS)
- **USB Ports** 2 x USB, EHCI, Rev. 2.0 compliant

Environment

- **Humidity** 95% @ 40° C (non-condensing)
- **Operating Temperature** (IEC 60068-2-2, 100% CPU/ I/O loading)
-20 ~ 65° C (-4 ~ 149° F) @ 5 ~ 85% RH
- **Shock Protection** IEC 68 2-27
CompactFlash: 50 G @ wall mount, half sine, 11 ms
HDD: 20 G @ wall mount, half sine, 11 ms
- **Vibration Protection** IEC 68 2-64 (Random 1 Oct./min, 1hr/axis.)
CompactFlash: 2 Grms @ 5 ~ 500 Hz,
HDD: 1 Grms @ 5 ~ 500 Hz

Ordering Information

- **UNO-2171-C11CE** Celeron M 1 GHz, 512 MB RAM Automation Computer
- **UNO-2171-P12CE** Pentium M 1.4 GHz, 1 GB RAM Automation Computer

Accessories

- **UNO-PCM22-AE** 2 x PC/104 expansion kit for UNO-2100 series
- **UNO-FPM21-AE** UNO-2000 series VESA mount kit
- **PCLS-DIAGAW10** Advantech Remote Monitoring & Diagnosis Utility