

MIC-1810

12-bit, 500 KS/s, 12-ch DAQ platform with Core™ i3/ Celeron® processor

NEW



Features

- 16 analog inputs, up to 800 kS/s, 12-bit resolution
- 2 analog outputs, up to 500 kS/s, 12-bit resolution
- Support for digital trigger and analog trigger
- 24 programmable digital I/O lines
- Two 32-bit programmable counter/timers
- Onboard FIFO memory (4k samples)
- 2 x RS-232 ports
- 2 x 10/100/1000 Base-T RJ-45 LAN ports
- 2 x USB 2.0 and 2 x USB 3.0 ports
- MIC-1810-S4A1E**
 - Intel Celeron® 1047UE Processor, 1.4GHz
- MIC-1810-S6A1E**
 - Intel Core™ i3-3217UE Processor 1.6GHz

Introduction

The MIC-1810 is a standalone automation controller with integrated data acquisition module and signal conditioning to provide digital I/O, analog I/O and counter functions. This controller also supports serial communication ports and several other networking interfaces. You can seamlessly integrate your applications into the MIC-1810 series and speed up your system development with these application ready controllers.

Specifications

Analog Input

- Channels** Single-ended: 16-ch; Differential: 8-ch
- Resolution** 12 bits
- Sample Rate** Single Channel: 800 kS/s max.; Multi-Channel: 500 kS/s max.

Note: The sampling rate for each channels will be affected by used channel number. For example, if 4 channels of MIC-1810 are used, the sampling rate is $500k/4 = 125$ kS/s per channel.

- Trigger Reference** Digital Trigger, Analog Trigger
- Trigger Mode** Start trigger, Delay to Start trigger; Stop trigger, Delay to Stop trigger
- FIFO Size** 4k samples
- Overvoltage Protection** 30 Vp-p
- Input Impedance** 1 GΩ
- Sampling Modes** Software and external clock
- Input Range** Software programmable

Gain	0.5	1	2	4	8
Unipolar	NA	0-10	0-5	0-2.5	0-1.25
Bipolar	±10	±5	±2.5	±1.25	±0.625
Gain Error (%FSR)	0.1	0.1	0.2	0.2	0.4

Analog Output

- Channels** 2-ch
- Resolution** 12 bits
- Sample Rate** 500 kS/s max.
- Output Range** Software programmable

Output Range	Internal Reference	0V-5V, 0V-10V, ±5V, ±10V	
	External Reference	Reference Input	Maximum Range
	Unipolar	0 ~ x V	
	Bipolar	-10V ≤ x ≤ 10V	-x V ~ x V

Digital I/O

- Channels** 24
- Compatibility** 5 V/TTL
- Input Voltage** Logic 0: 0.8 V max. Logic 1: 2.0 V min.
- Output Voltage** Logic 0: 0.8 V max. Logic 1: 2.0 V min.
- Output Capability** Sink: 15 mA @ 0.8 V Source: 15 mA @ 2.0 V

Counter

- Channels** 2
- Resolution** 32 bits
- Compatibility** 5 V/TTL
- Max. Input Frequency** 10 MHz
- Pulse Generation** Yes
- Timebase Stability** 50 ppm

General

- Dimensions (W x D x H)** 165 x 130 x 59 mm
- Power Consumption** 45 W (Typical)
- Power Requirements** Single 12V_{DC} power input
- Weight** 2.4 kg (Typical)
- OS Support** Windows 7

System Hardware

- CPU** Intel Celeron® 1047UE Processor 1.4GHz (MIC-1810-S4A1E) Intel Core™ i3-3217UE Processor 1.6GHz (MIC-1810-S6A1E)
- Memory** 4G SO-DDR3-1600
- Indicators** LEDs for Power, IDE and LAN (Active, Status)
- Keyboard/Mouse** USB
- Storage** SSD: 1 x 2.5" SSD

Environment

- Storage Humidity** 5 ~ 95% RH, non-condensing
- Operating Temperature** 0 ~ 50°C (14 ~ 140°F) @ 5 ~ 85% RH with 0.7m/s air flow
- Storage Temperature** -20 ~ 80°C (-4 ~ 176°F)

Ordering Information

- MIC-1810-S4A1E** Data Acquisition Computer with Intel® Celeron® 1047UE processor
- MIC-1810-S6A1E** Data Acquisition Computer with Intel® Core™ i3-3217UE processor

Optional Accessories

- 1700001714** Power Cord BSMI 3P 7A 125V 18AWG 180CM
- 1702002600** Power Cord 3P UL/CSA(USA) 125V 10A 1.83M 180D
- 1700023535-01** Power Cord CCC 3P 16A 250V 183cm
- 1960077844N001** Table Mount (W x L: 130 x 175 mm)