# 2U-2000/602

# 2U 6-Slot Rackmount Chassis with Front USB and PS/2 Interfaces



### **Features**

- 2U rackmount chassis supports up to 6 cards
- Butterfly backplane design
- Front-accessible USB and PS/2 connectors
- 250W / 300W AC ATX and DC power supply options
- Two 40 CFM cooling fans with air filter
- Lockable front door prevents unauthorized access

#### Features with ACP-2000 only:


- System alarm notification by front LED indicators
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

### **Specifications**

Drive Bay		External	Internal	
	Slim Optical Disk Drive	1/-	-	
	3.5"	2/1	-/1	
	5.25"	-/1	-	
Cooling	Fan	2 (8 cm / 47 CFM each) / 2 (8 cm / 40 CFM each)		
	Air Filter	Yes		
Front I/O Interface	USB	2		
	PS/2	1		
Miscellaneous	LED Indicators	Power and HDD activity; fan and temperature for ACP-2000 only		
	Rear Panel	One 9-pin D-Sub opening		
Intelligent System Module Remote Monitoring	CPU/System fan speed , CPU/System temper			
	(Only selected Advantech MBs/CPU cards with SUSIAccess installed can fully enable these functions, check with Advantech local rep. for detailed information.) (This feature only enabled in ACP-2000)			
Environment		Operating	Non-Operating	
	Temperature	0 ~ 40° C (32 ~ 104° F)	-20 ~ 60° C (-4 ~ 140° F)	
	Humidity	10 ~ 85% @ 40° C, non-condensing	10 ~ 95% @ 40° C, non-condensing	
	Vibration (5 ~ 500 Hz)	0.5 Grms	2 G	
	Shock	10 G (with 11 ms duration, half sine wave)	30 G	
Physical Characteristics	Dimensions (W x H x D)	482 x 88 x 451 mm (19" x 3.5" x 17.8")		
	Weight	11.5 kg (25.3 lb) / 11.3 kg (24.9 lb)		

### **Front View**


## Inside View



**GST** Industrial Chassis

All product specifications are subject to change without notice

### 2U-2000/602



### **Ordering Information**

Part Number	Power Supply	Backplane		
PICMG 1.0				
2U-2000P3-00BE	Without power supply, with ATX switch	989K610622E (PCA-6106P3V)		
2U-2000P4-00BE	Without power supply, with ATX switch	989K610512E (PCA-6105P4V)		
PICMG 1.3				
2U-2000EBP-00BE	Without power supply, with ATX switch	-		
2U-602EBP-00XBE	Without power supply, with ATX switch	-		

## **Power Supply Options**

Part Number	80 Plus Grade	Wattage	Туре	Input
PS8-300ATX-ZBE	Bronze	300W	Single	AC 100 ~ 240 V (full range)
PS8-400ATX-ZE	Bronze	400W	Single	AC 100 ~ 240 V (full range)
PS-300ATX-DC48E	-	300W	Single	DC -48 V
RPS-300ATX-ZE (ACP-2000 only)	-	300W	(1+1) Redundant	AC 100 ~ 240 V (full range)

## **Optional Accessories**

Part Number	Description
1950000868T00B	P3 card cage
1950000869N002	P4 card cage
96CB-SATAPOWER-6P1	SATA power wire 6-pin to big 4-pin (for slim ODD)
IPC-DT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays

### **Spare Parts**

Part Number	Description
2130006189S000	Filter behind the door 156 x 45 x 5 mm
1990001949	Filter in the front of the fans 165 x 58 mm